



www.shure.eu ©2018 Shure Europe GmbH AL20018SE SHURE

⇔ Name STD

Channel1

6:29) sil

ADX1M

#### SHURE



# AXIENT DIGITAL INTEGRITY YOU CAN HEAR.



SHURE

AD1

hannel

## IT'S A COMPLEX WORLD FOR WIRELESS MICROPHONES.

The RF environment is ever-changing – jammed with TV transmissions, mobile devices, and other wireless equipment. And it's becoming more congested and unpredictable every day.

# AXIENT<sup>®</sup> DIGITAL MAKES IT PERFECTLY CLEAR.

Incorporating the most innovative wireless audio technology in the world, Axient Digital was engineered from the ground up for professional productions that demand flawless execution.

With an unprecedented level of signal stability and audio clarity, plus flexible hardware options, advanced connectivity, and comprehensive control, it's a wireless system built to take on the challenges of today – and tomorrow.

# AXIENT® DIGITAL ONE SYSTEM. POWERFUL POSSIBILITIES.

With two transmitter series to choose from – both compatible with a shared receiver platform – Axient Digital is a scalable wireless system that provides incomparable sound for a wide range of applications and settings.

#### **AD Series Transmitters**

### ACCESSIBLE PERFORMANCE.

Offering a variety of core benefits including high- performance RF, digital audio, and networking, Axient Digital with AD series transmitters represents the new standard in professional wireless. Powered by either AA or SB900A rechargeable batteries, these transmitters fit easily into existing workflow.



### ADX Series Transmitters TRANSFORMATIONAL TECHNOLOGY.

Critical applications call for the enhanced features of the ADX series. With form factors that include a frequency diversity handheld and the first micro bodypack with an internal antenna, these ShowLink®enabled transmitters offer real-time remote control plus automatic interference detection and avoidance.

#### **RF** Protection

With outstanding signal quality in even the most complex, congested environments, Axient<sup>®</sup> Digital ensures maximum stability, range, and clarity for uncompromising audio anywhere, every time.

#### Next-Gen Digital Radio + Channel Quality Metering

A high-performance modulation scheme provides maximum signal stability. The 5-segment Channel Quality meter allows for real-time analysis of RF signalto-noise, enabling operating range assessments and visibility into potential interference.

#### Spectral Efficiency

RELABILITYS

A robust High Density transmission mode increases system channel count dramatically – with up to 63 active channels per 8 MHz TV band (47 channels/6 MHz) all while maintaining exceptional audio quality.

#### **Operating Range**

#### True Digital Diversity

Mounting a better defense against multipath, fading events, and other RF anomalies, Axient Digital combines two discrete RF signals per receiver channel using a quality-based maximal-ratio-combining algorithm.

Selectable transmission modes and power levels enable optimum range and audio quality, with analogtype resilience, artifact-free muting, and fast signal recovery at end of range.

#### Quadversity™

By assigning four antenna inputs to a single channel via patented technology, Quadversity<sup>™</sup> can provide extended coverage and the option for separate zones, plus added resistance against multipath interference and RF noise.

#### Wide Tuning Receivers and Transmitters

An expansive tuning bandwidth of up to 184MHz across all receivers and transmitters supplies broad strategic spectrum coverage, while simplifying inventories for both sellers and operators.

#### **Frequency Diversity**

Signal quality is maximized by transmitting two identical signals on independent frequencies. If the active signal degrades, the other takes over automatically. With the ADX2FD handheld transmitter, Axient Digital uses a patented technique to monitor and combine the transmissions for a flawless audio signal.

#### Interference Detection and Avoidance

With real-time monitoring via the AXT600 Spectrum Manager, sound engineers can neutralize RF interference by manually switching the signal to a clear backup frequency, or by programming the system to do it automatically.

## Audio Quality

Axient<sup>®</sup> Digital defies limitations for both RF and audio quality. With industry-leading low latency, transparent frequency response, and wide dynamic range, nothing gets in the way of true, pure sound. No matter the setting, it's Shure audio quality you can count on.



A best-in-class 2 milliseconds from microphone transducer to analog output guarantees seamless, cohesive sound.\*

Encryption

HEAR NOTHING BUT QUALITY.

\*Latency is mode dependent. High Density mode latency is 2.9 ms.

#### **Transparent Sound**

A flat frequency response over a wide range from 20Hz to 20kHz provides accurate audio reproduction.

#### **Digital Outputs**

Dante<sup>™</sup> and AES67 digital audio transmits via a configurable 4-port switch for combined control / audio or separate streams with redundancy. AES3 output provides an additional option for pristine digital audio.

#### Dynamic Range

Wide dynamic range of >120 dB yields impressive signal-to-noise performance and accurate transient response.

An Advanced Encryption Standard (AES) 256-bit encrypted signal ensures that every transmission is secure and unbreachable.



### **Command and Control**

ShowLink<sup>®</sup> remote control, Wireless Workbench<sup>®</sup>, the ShurePlus<sup>™</sup> Channels app, and networked battery monitoring provide unmatched control and insight, for seamless performance.

SEE

#### Wireless Workbench and the ShurePlus Channels App

Wireless Workbench offers total control - with an enhanced interface, access to advanced RF spectrum and Timeline plotting, frequency coordination, and live performance monitoring. Control and monitor capabilities can also be extended to a mobile device with the ShurePlus Channels iOS app.

control booth.

#### ShowLink Remote Control

ADX transmitters with ShowLink give engineers comprehensive real-time remote control of all transmitter parameters using a robust 2.4GHz diversity wireless connection, so settings can be changed right from the

#### Dante<sup>™</sup> Cue and Dante<sup>™</sup> Browse

With the push of a button, Dante Cue enables monitoring of every Axient Digital channel on the network through a single headphone output. Plus, Dante Browse offers high-fidelity monitoring of any Dante-enabled device on the network.

#### Networked Charging

Smart, high-performance batteries and chargers provide detailed visibility and remote monitoring of critical parameters such as remaining runtime in hours and minutes and charging status.



### Receivers

# SCALABLE.

One receiver platform is the gateway to the full range of features, from high-performance RF and transparent digital audio, to software control. With Quadversity<sup>™</sup>, the AD4Q can assign four antennas to a single channel for greater coverage and signal quality.





#### AD4D AD4Q Four-Channel Receiver **Two-Channel Receiver**

- Compatible with all AD and ADX transmitters
- Wide tuning range up to 184MHz
- True digital diversity reception per channel for drop-out resistance
- Networked control with Wireless Workbench<sup>®</sup> and ShurePlus<sup>™</sup> Channels app
- Quadversity<sup>™</sup> mode for extended antenna coverage and improved RF signal-to-noise (AD4Q only)
- DC module version available to support redundant power





## **AD Series Transmitters**

# ACCESSIBLE.

AD series handheld and bodypack transmitters put professional-quality wireless digital audio within reach, with breakthrough RF performance and wide tuning up to 184MHz.

# AD1

#### Bodypack Transmitter

- Two transmission modes:
- Standard for optimal coverage
- New High Density mode for maximum system channel count and robust coverage
- Encryption-enabled, secure transmission
- External contacts for docked charging
- AA or SB900A Li-ion rechargeable batteries



Detachable <sup>1</sup>/4-wave antenna





Backlit LCD with easy-to-navigate menu and controls

## AD2

#### Handheld Transmitter

• Two transmission modes:

Standard for optimal coverage

New High Density mode for maximum system channel count and robust coverage

• Encryption-enabled, secure transmission

Frequency and power lockout

 Rugged metal construction in black or nickel finish

• External contacts for docked charging

AA or SB900A Li-ion rechargeable batteries



Also available with these Shure microphone cartridges



KSM9, KSM9HS (In black or nickel)



BETA **87A**, BETA **87C** 



BETA **58A** 



SM58



Low-profile, lockable power switch

KSM8 Nickel VP**68** 

### **ADX** Series Transmitters

# TRANSFORMATIONAL.

All ADX transmitters set the stage for exceptional performance, with wide tuning up to 184MHz, interference protection, advanced rechargeability, streamlined design, and ShowLink<sup>®</sup> remote control for real-time parameter adjustments right from the booth.



# ADX1

#### Bodypack Transmitter

- Slim, light design with powerful features
- Advanced control menu, removable antenna, fully concealed buttons and switch
- Durable, moisture-resistant, lightweight metal case
- SB910 rechargeable batteries for up to 10 hours of runtime
- External contacts for docked
- Diversity ShowLink-enabled for remote transmitter control and automatic interference avoidance



### ADX2 Handheld Transmitter

- Sleek design with powerful features
- Durable, moisture-resistant, lightweight metal case, available in Black and Nickel finish
- SB920 rechargeable batteries for up to 9 hours of runtime
- External contacts for docked charging, with optional fully-covered radome
- Diversity ShowLink-enabled for remote transmitter control and automatic interference avoidance





## ADX2FD

#### **Frequency Diversity** Handheld Transmitter

- Able to transmit RF signal on two discrete carriers
- Optional 50mW high-power mode drives a single frequency with increased power
- Durable, moisture-resistant. lightweight metal case, available in Black and Nickel finish
- Up to 6.5 hours of runtime with SB920 rechargeable batteries when transmitting on two RF carriers (up to 9 hours battery life when transmitting on a single RF carrier)
- External contacts for docked charging, with optional fully-covered radome
- Diversity ShowLink-enabled for remote transmitter control and automatic interference avoidance

KSM8 Black or Nickel






ADX2F

hannel'

1000

KSM8

Black or Nickel





KSM9, KSM9HS (In black or nickel)



#### BETA 87A. BETA 87C



BETA **58A** 







# System Management **POWERFUL**.

Axient<sup>®</sup> Digital offers unprecedented remote control and monitoring for easy coordination of clean, useable frequencies no matter what kind of RF environment you face.



# **AXT600**

#### Spectrum Manager

- Single rack unit delivers wide-band UHF spectrum scanning and analysis plus compatible frequency coordination
- Scans and analyzes the global UHF spectrum (470-952 MHz) in approximately one minute
- Continuously monitors, evaluates, and displays backup frequencies in real time
- Is compatible with Axient Digital and other Shure networked wireless systems

# AD610

#### Diversity ShowLink® Access Point

- Wireless network connectivity between all linked transmitters and receivers
- Enables real-time wireless remote control of up to 24 transmitters per access point
- ShowLink offers ability to adjust gain, change frequencies, mute signals, and more
- True diversity antenna scheme maintains a robust link in the 2.4GHz frequency range
- Automatic channel selection scans the 2.4GHz range for the best channel
- Automatic frequency agility moves the network to the best available channel if signal degrades
- Is compatible with Axient Digital ADX series and Axient analog systems

#### Additional Accessories

- Batterv sleds
- Radome covers

SHURE AD610

AXIENT DIGITAL

ShowLink Access Point

9....

- Locking power cords
- ShowLink Talk switches for handhelds and bodypacks

• • • 2<sup>7</sup> ① 器





## SBRC



2-bay dock charger

SB900A batteries

# **RECHARGEABLE.**

A range of networked battery solutions for AD and ADX transmitters includes the rack-mounted SBRC and a series of units that support individual and docked charging.


#### **Rackmount Charging Station**

- Accommodates eight Li-ion batteries in a single rack space
- Front-panel display for battery parameters including time-to-full in hours and minutes and percent-of-capacity
- · Remote monitoring via Shure Wireless Workbench



# SBC200

(AD1 and AD2)



SBC240

2-bay dock charger

SB910 batteries (ADX1)

(ADX2 and ADX2FD)

Shure Wireless Workbench

# SBC220

States -

## 2-bay dock charger

- SB900A batteries (AD1 and AD2)
- SB920 batteries Remote monitoring via Shure Wireless Workbench Remote monitoring via

- SBC-AX Charging module for SB900A (AD1 and AD2)
- SBM910 Charging module for SB910 (ADX1)
- SBM920 Charging module for SB920 (ADX2 and ADX2FD)
- SBM910M Charging module for SB910M (ADX1M micro bodypack)



# SBC800

#### 8-bay charger

 SB900A batteries (AD1 and AD2)



# SBC840

#### 8-bay charger

- SB910 batteries (ADX1)
- SB920 batteries (ADX2 and ADX2FD)
- Remote monitoring via Shure Wireless Workbench



## SBC**840M** 8-bay charger

- SB910M batteries (ADX1M micro bodypack)
- Remote monitoring via Shure Wireless Workbench